


剖面 A-A



剖面 B-B

Specifications:
 Operating Voltage: 250V AC/DC
 Current Rating: 2A AC/DC
 Withstand Voltage: 800V AC/Minute
 Contact Resistance: $\leq 20m\Omega$
 Insulation resistance: $\geq 500m\Omega$
 Operating Temperature: $-25^{\circ}C \sim +85^{\circ}C$
 Material: Phosphoric copper Tin-plated
 Applicable Wire Sizes: AWG30# ~ 22#

一般公差 TOLERANCES X. ± 0.40 .XX ± 0.20 .X ± 0.30 .XXX ± 0.10 ANGLES $\pm 2^{\circ}$		深圳市宏利电子有限公司 Shenzhen Holy Electronic Co.,Ltd	
检验尺寸标示 SYMBOLS $\text{\textcircled{C}}$ $\text{\textcircled{M}}$ INDICATE CLASSIFICATION DIMENSION $\text{\textcircled{C}}$ MARK IS CRITICAL DIM. $\text{\textcircled{M}}$ MARK IS MAJOR DIM.	工程 图号 PH20TE 品名 PH2.0 端子 TITLE PH2.0mm Pitch Terminal	制图 (DR) '10/03/22 审核 (CHKD) 核准 (APPD) Rigo Lu	张数 (SHEET) 1 OF 1 单位 (UNITS) mm
表面处理 (FINISH) 比例 (SCALE) 1:1	单位 (UNITS) mm		张数 (SHEET) 1 OF 1 单位 (UNITS) mm

修订 REV 修改摘要 REVISION DESCRIPTION 日期 DATE 签名 SIGNATURE	日期 DATE 签名 SIGNATURE
--	-------------------------------