



A-A



B-B



C-C

Specifications:

- Operating Voltage: 250V AC/DC
- Current Rating: 3A AC/DC
- Withstand Voltage: 1000V AC/Minute
- Contact Resistance: $\leq 30\text{m}\Omega$
- Insulation resistance: $\geq 1000\text{m}\Omega$
- Operating Temperature: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- Material: Phosphoric copper Tin-plated
- Applicable Wire Sizes: AWG30# ~ 22#

一般公差 TOLERANCES X. ± 0.40 .XX ± 0.20 .X ± 0.30 .XXX ± 0.10 ANGLES $\pm 2^{\circ}$		深圳市宏利电子有限公司 Shenzhen Holy Electronic Co.,Ltd	
检验尺寸标示 SYMBOLS \odot \ominus INDICATE CLASSIFICATION DIMENSION \odot MARK IS CRITICAL DIM. \ominus MARK IS MAJOR DIM.		工程 图号 HY20TE	制图 (DR) *10/03/22 审核 (CHKD)
表面处理 (FINISH)		品名 HY2.0 端子	核准 (APPD) Rigo Lu
比例 (SCALE) 1:1		单位 (UNITS) mm	张数 (SHEET) 1 OF 1 尺寸 (SIZE) A4 版本 (REV) 0

修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	签名 SIGNATURE
-	-	-	-