



PCB 寸法

Specifications:
 Operating Voltage: 250V AC/DC
 Current Rating: 7A AC/DC
 Withstand Voltage: 1000V AC/Minute
 Contact Resistance: $\leq 20\text{m}\Omega$
 Insulation resistance: $\geq 1000\text{m}\Omega$
 Operating Temperature: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

孔数	A	B
2	3.96	7.92
3	7.92	11.88
4	11.88	15.84
5	15.84	19.80
6	19.80	23.76
7	23.76	27.72
8	27.72	31.68
9	31.68	35.64
10	35.64	39.60
11	39.6	43.56
12	43.56	47.52

一般公差
 TOLERANCES
 X. ± 0.40 .XX ± 0.20
 .X ± 0.30 .XXX ± 0.10
 ANGLES $\pm 2^{\circ}$

深圳市宏利电子有限公司
 Shenzhen Holy Electronic Co.,Ltd

检验尺寸标示
 SYMBOLS \odot \ominus INDICATE
 CLASSIFICATION DIMENSION

工程图号
 VH396-nA

制图 (DR)
 10/03/22
 审核 (CHKD)

\odot MARK IS CRITICAL DIM.
 \ominus MARK IS MAJOR DIM.

品名
 VH3.96-nAW 直针

核准 (APPD)
 Rigo Lu

表面处理 (FINISH)

TITLE
 VH3.96mm Pitch A DIP
 CONN

张数 (SHEET)
 1 OF 1

比例 (SCALE)
 1:1

单位 (UNITS)
 mm

尺寸 (SIZE)
 A4
 版本 (REV)
 0

修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	签名 SIGNATURE
-	-	-	-